Product data sheet Characteristics

48145

rear connection upside horizontal mounting - for NW 40 - 3 poles



Main	
Product or component type	Rear connection
Accessory / separate part category	Connection accessory
Range compatibility	Masterpact NW Masterpact NW40 switch
	disconnector
	Masterpact NW Masterpact NW40 circuit breaker
Poles description	3P
[In] rated current	4000 A H1 drawout
	4000 A H2 drawout
	4000 A H2A drawout
	4000 A H10 drawout
	4000 A H1b drawout
	4000 A H3 drawout
	4000 A H1 fixed
	4000 A H2 fixed
	4000 A H2A fixed
	4000 A H1b fixed
	4000 A HA drawout
	4000 A HF drawout
	4000 A HA10 drawout
	4000 A HA fixed
	4000 A HF fixed
	4000 A HA10 fixed

Complementary

Location of connection	Rear	
Localisation on device	Upside	
Connection position	Horizontal	
Connection pitch	115 mm	

Offer Sustainability

REACh Regulation	☑ REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	₽¥Yes	
China RoHS Regulation	China RoHS Declaration	

Contractual warranty

Ochitacidal Warranty		
Warranty	18 months	