



### Main

Device short name	Current transformer module
Product or component type	Current transformer
Device application	Control
Range compatibility	ComPact NSX160 ComPact NSX250 INS250 Compact INV100...250
Poles description	4P
[In] rated current	150 A
Current transformer ratio	150/5 A
Power consumption in VA	3 VA
Accuracy class	Class 4.5

### Complementary

Auxiliary connection terminal	Cable connector 2.5 mm <sup>2</sup>
-------------------------------	-------------------------------------




### Environment

Electrical shock protection class	Class II
IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK04 conforming to IEC 62262

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1.16 kg
Package 1 Height	14 cm
Package 1 width	14.5 cm
Package 1 Length	17.5 cm
Unit Type of Package 2	S03
Number of Units in Package 2	4
Package 2 Weight	5.127 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 <a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	 <a href="#">Yes</a>
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>

---

Circularity Profile

 [End Of Life Information](#)

---

WEEE

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

---

### Contractual warranty

---

Warranty

18 months

---