LV431567

current transformer module - 250 A - 3 poles for NSX100...250





Main

Mairi	
Device short name	Current transformer module
Product or component type	Current transformer
Device application	Control
Range compatibility	ComPact NSX250
Poles description	3P
[In] rated current	250 A
Current transformer ratio	250/5 A
Power consumption in VA	5 VA
Accuracy class	Class 4.5

Complementary

Auxiliary connection terminal	Cable connector 2.5 mm²
-------------------------------	-------------------------

Environment

Electrical shock protection class	Class II
IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK04 conforming to IEC 62262

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	1.04 kg	
Package 1 Height	13.5 cm	
Package 1 width	14.5 cm	
Package 1 Length	17.5 cm	
Unit Type of Package 2	S03	
Number of Units in Package 2	4	
Package 2 Weight	4.647 kg	
Package 2 Height	30 cm	
Package 2 width	30 cm	
Package 2 Length	40 cm	

Offer Sustainability

Green Premium product	
☐ REACh Declaration	
Compliant EEU RoHS Declaration	
Yes	
₫Yes	
☑ China RoHS Declaration	
Product Environmental Profile	
	Compliant EVEU RoHS Declaration Yes Ves China RoHS Declaration

Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Contractual warranty	
Warranty	18 months