



Main

| | |
|---------------------------|----------------------------|
| Device short name | Current transformer module |
| Product or component type | Current transformer |
| Device application | Control |
| Range compatibility | ComPact NSX630 |
| Poles description | 3P |
| [In] rated current | 630 A |
| Current transformer ratio | 630/5 A |
| Power consumption in VA | 8 VA |
| Accuracy class | Class 4.5 |

Complementary

| | |
|-------------------------------|-------------------------------------|
| Auxiliary connection terminal | Cable connector 2.5 mm ² |
|-------------------------------|-------------------------------------|

Environment

| | |
|-----------------------------------|------------------------------|
| Electrical shock protection class | Class II |
| IP degree of protection | IP40 conforming to IEC 60529 |
| IK degree of protection | IK04 conforming to IEC 62262 |

Packing Units

| | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 2.28 kg |
| Package 1 Height | 14 cm |
| Package 1 width | 17 cm |
| Package 1 Length | 20 cm |
| Unit Type of Package 2 | S03 |
| Number of Units in Package 2 | 2 |
| Package 2 Weight | 5.047 kg |
| Package 2 Height | 30 cm |
| Package 2 width | 30 cm |
| Package 2 Length | 40 cm |

Offer Sustainability

| | |
|----------------------------|---|
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Contractual warranty

Warranty

18 months
