



Main

Range	Masterpact
Range of product	Masterpact NW DC
Product or component type	Control unit
Trip unit name	Micrologic DC 1.0
Trip unit technology	Electronic
Range compatibility	Masterpact NW10...40 DC
Device application	Distribution
Number of poles	3P
Protection type	For instantaneous short-circuit protection
Trip unit rating	1000 A 2000 A 4000 A
Network type	DC
Circuit breaker mounting mode	Drawout

Complementary

Instantaneous protection pick-up adjustment type li	Adjustable
[li] instantaneous protection pick-up adjustment range	2500...5400 A
Earth-leakage protection	Without

Environment

Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-50...85 °C

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.