



Main

Range	ComPact
Product name	ComPact NSX DC
Range of product	ComPact NSX400...630 DC
Device short name	NSX1000 DC
Product or component type	Circuit breaker
Device application	Distribution
Number of poles	2P
Protected poles description	2t
[In] rated current	1000 A at 40 °C
[Ue] rated operational voltage	600 V DC
Network type	DC
Suitability for isolation	Yes conforming to EN/IEC 60947-2
Utilisation category	Category A
[Icu] rated ultimate short-circuit breaking capacity	50 kA Icu at 250 V DC 1P conforming to IEC 60947-2 50 kA Icu at 600 V DC 2P conforming to IEC 60947-2
Performance level	N 50 kA 250 V DC
Trip unit name	TM-DC
Trip unit technology	Thermal-magnetic
Control type	Toggle
Circuit breaker mounting mode	Fixed

Complementary

[Ui] rated insulation voltage	750 V DC conforming to IEC 60947-2
[Uimp] rated impulse withstand voltage	8 kV conforming to IEC 60947-2
[Ics] rated service short-circuit breaking capacity	4.5 kA at 600 V DC conforming to IEC 60947-2
Mechanical durability	5000 cycles
Electrical durability	1000 Cycles at 600 V In 2000 cycles at 600 V In/2
Mounting support	Backplate
Upside connection	Front
Downside connection	Front
Connection pitch	45 mm
Protection type	L : for overload protection (thermal) I : for short-circuit protection (magnetic)
Trip unit rating	1000 A at 40 °C
Long-time pick-up adjustment type Ir (thermal protection)	Adjustable
[Ir] long-time protection pick-up adjustment range	0.7...1 x In
Earth-leakage protection	Without
Width (W)	185 mm
Height (H)	488 mm
Depth (D)	110 mm
Net weight	8.3 kg

Environment

Standards	EN/IEC 60947
Product certifications	CCC EAC Marine
Overvoltage category	Class II
Electrical shock protection class	Class II
Pollution degree	3 conforming to IEC 60664-1
IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK07 conforming to IEC 62262
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-50...85 °C
Relative humidity	0...95 %
Operating altitude	0...2000 m without derating 2000 m...5000 m with derating

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	7.9 kg
Package 1 Height	15.8 cm
Package 1 width	19.6 cm
Package 1 Length	36.8 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins