



## Main

Range of product	PowerPact L
Product or component type	Circuit breaker
Trip Unit Type	Magnetic
Interrupt Code	G

## Complementary

Line Rated Current	400 A
Number of Poles	3P
Interrupt Rating	20 kA at 500 V DC 35 kA at 480Y/277 V AC
Voltage Rating	500 V DC
Protection technology	Current limiter
Mounting mode	Unit mount
Electrical connection	Lugs load Lugs line
Magnetic tripping current	1000...2000 A
Terminal Type	AL400L61K4
Wire Size	AWG 2...500 kcmil (aluminium) for 1 cable(s) AWG 2...600 kcmil (copper) for 1 cable(s)
Tightening torque	50 N.M for 35...240 mm <sup>2</sup> (AWG 2...500 kcmil) 50 N.m for 35...300 mm <sup>2</sup> (AWG 2...600 kcmil)
Height	340.11 mm
Width	184.66 mm
Depth	167.89 mm

## Environment

Product certifications	CSA 22-2 CCC IEC CE UL 489 NMX NEMA
------------------------	---

## Packing Units

Package 1 Weight	11.567 kg
Package 1 Height	34.131 cm
Package 1 width	18.733 cm
Package 1 Length	79.851 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
PVC free	Yes

## Contractual warranty

Warranty	18 months
----------	-----------