



Main

Range of product	PowerPact L
Product or component type	Circuit breaker
Trip Unit Type	Magnetic
Interrupt Code	L

Complementary

Line Rated Current	800 A
Number of Poles	4P
Interrupt Rating	50 kA at 500 V DC
Voltage Rating	500 V DC
Protection technology	Current limiter
Mounting mode	Unit mount
Electrical connection	Lugs load Lugs line
Magnetic tripping current	2000...4000 A
Terminal Type	AL600LS52K4
Wire Size	AWG 2/0...500 kcmil (aluminium) for 1 cable(s) AWG 2/0...600 kcmil (copper) for 1 cable(s)
Tightening torque	50 N.m for 70...240 mm ² (AWG 2/0...500 kcmil)
Height	340.11 mm
Width	184.66 mm
Depth	167.89 mm

Environment

Product certifications	CSA 22-2 CCC IEC CE UL 489 NMX NEMA
------------------------	---

Packing Units

Package 1 Weight	10.977 kg
Package 1 Height	34.131 cm
Package 1 width	18.733 cm
Package 1 Length	79.851 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------