



Main

Range	TeSys
Device short name	LA4SK
Product or component type	Suppressor module
Product compatibility	CA2SK LC1SK06 CA3SK LP1SK06 LC1SKGC
Suppressor technology	Diodes
Quantity per set	Set of 10

Complementary

Mounting location	Right hand side
[Uc] control circuit voltage	24...250 V DC
Maximum peak voltage	1 Uc
Net weight	0.003 kg

Environment

Ambient air temperature for operation	-20...50 °C
Ambient air temperature for storage	-50...70 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	3 g
Package 1 Height	3.5 cm
Package 1 width	6 cm
Package 1 Length	14.3 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	30 g
Package 2 Height	3.5 cm
Package 2 width	6 cm
Package 2 Length	14.3 cm
Unit Type of Package 3	S01
Number of Units in Package 3	190
Package 3 Weight	773 g
Package 3 Height	15 cm
Package 3 width	15 cm
Package 3 Length	40 cm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------