



Main

| | |
|---------------------------|--|
| Range | TeSys |
| Device short name | LAD4 |
| Product or component type | Suppressor module |
| Product compatibility | 3P LC1D40A...D80A 4P LC1DT60A...DT80A |

Complementary

| | |
|------------------------------|---------------------------------------|
| Mounting location | Front |
| Mounting mode | By clips |
| Suppressor technology | Bidirectional peak limiting diode |
| [Uc] control circuit voltage | 25...72 V DC 25...72 V AC 50/60 Hz |
| Maximum peak voltage | 2 Uc |
| Net weight | 0.02 kg |

Environment

| | |
|---------------------------------------|-------------|
| Ambient air temperature for operation | -25...55 °C |
| Ambient air temperature for storage | -40...80 °C |

Packing Units

| | |
|------------------------------|------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 19 g |
| Package 1 Height | 2 cm |
| Package 1 width | 3 cm |
| Package 1 Length | 5 cm |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Contractual warranty

Warranty

18 months
